



Common Corridor





Basement Carpark

Office

Office Lounge

Living Room

# Light Up with LED!

-  **Eco-friendly** as LED does not contain mercury
-  Up to **80%** savings in energy
-  Lasts **50 times** longer than conventional lights
-  No replacement for up to **20 years**  
(based on usage of 6hr/day)



## Surface Mounted Lights



**LF 212 / LF 424**  
2-foot & 4-foot LED  
Surface Mounted Lights



**LF 212-S / LF 424-S**  
2-foot & 4-foot LED  
Surface Mounted Lights  
(with Sensor)

## T8 Tubes



**LT 8A-212 / LT 8A-424 / LT 8A-530**  
2-foot / 4-foot / 5-foot Super Bright  
LED Tube

## Downlights



**LDR 615 / LDR 623**  
6-inch Circular LED  
Downlights

## Floodlights



**XL 10 / XL 25**  
LED Floodlight



**XL 10S / XL 25S**  
LED Sensor Floodlight

## Bulbs



**AZCEND Globe**  
5-Watt & 7-Watt LED  
Light Bulbs



**AZCEND Spot**  
6-Watt LED Spotlight

**Choose AZ e-lite LED Lighting to enjoy savings in electricity bills and reduce impact on our environment!**

# AZ e-lite

A Member of Aztech Group

# Light Up with LED!

# Aze-lite

A Member of Aztech Group



	LF 212	LF 424
<b>Lumen</b>	600-700lm	1200-1400lm
<b>Power Consumption</b>	12W	24W
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)	
<b>Life Span / IP Rating</b>	50,000 hours / IP54	
<b>Dimension (mm) LxWxH</b>	601 x 60 x 78	1202 x 60 x 78

## LF 212 / LF 424

### 2-foot / 4-foot LED Surface Mounted Light

- Perfect replacements for 2-foot / 4-foot T8 fluorescent fixtures
- Suitable for outdoor and car park lighting
- High efficiency LED module offers 50% energy saving
- Anti-rust solid metal housing
- Certified by TUV-SUD to meet stringent quality standard
- PR12 outdoor durable polyester powder coating
- IP54 compliant - dust-proof, splash-proof and insect-proof



	LF 212-S	LF 424-S
<b>Lumen</b>	600-700lm	1200-1400lm
<b>Power Consumption</b>	12W(ON)/4W (Standby)	24W(ON)/8W (Standby)
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)	
<b>Life Span / IP Rating</b>	50,000 hours / IP54	
<b>Dimension (mm) LxWxH</b>	678 x 60 x 78	1279 x 60 x 78

## LF 212-S / LF 424-S

### 2-foot / 4-foot LED Surface Mounted Light (with Sensor)

- Dual sensors mounted on both ends to provide bi-directional sensing
- Suitable for outdoor lighting such as emergency tunnels, corridors and staircases
- Consumes only 30% of energy in absence of human traffic
- Anti-rust solid metal housing
- PR12 outdoor durable polyester powder coating
- IP54 compliant - dust-proof, splash-proof and insect-proof



	LT 8A-212	LT 8A-424	LT 8A-530
<b>Lumen</b>	800-850lm	1550-1700lm	1950-2100lm
<b>Power Consumption</b>	12W	24W	30W
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)		
<b>Life Span</b>	35,000 hours		
<b>Tube Length</b>	2-foot	4-foot	5-foot

## LT 8A-212 / LT 8A-424 / LT 8A-530

### 2-foot / 4-foot / 5-foot Super Bright LED Tube

- Direct replacement for T8 fluorescent tube without the need for ballast or starter
- Suitable for office, shop, corridor and car park lighting
- All plastic design prevents electrical shock
- Even light distribution with no flicker
- No mercury content
- 60% energy saving



	LDR 615	LDR 623
<b>Lumen</b>	500~600lm	800~1100lm
<b>Power Consumption</b>	15W	23W
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)	
<b>Life Span</b>	35,000 hours	
<b>Dimension (mm) DiaxH</b>	240 x 78.5	

## LDR 615 / 623

### 6-inch LED Circular Downlight

- LED recess-mounted downlights for general 2 x 13W CFL downlight replacement
- Suitable for office, shop, household and corridor lighting
- Rugged aluminium die cast casing
- PR12 outdoor durable polyester powder coating
- Specially designed diffuser with ORSRAM LEDs
- 40% energy saving



	XL 10	XL 25
<b>Lumen</b>	1300lm	2800lm
<b>Power Consumption</b>	30W	65W
<b>Colour Temperature</b>	6500K (Daylight)	
<b>Life Span / IP Rating</b>	35,000 hours / IP54	
<b>Dimension (mm) HxWxD</b>	218 x 212 x 211	299 x 214 x 211

## XL 10 / XL 25

### LED Floodlight

- Eco-friendly floodlight suitable for indoor and outdoor applications
- Replacement for 150W and below conventional floodlights
- Suitable for rugged outdoor use
- IP54 compliant - dust-proof, splash-proof and insect-proof
- Separate pan and tilt adjustment gives maximum flexibility for illumination
- 40% energy saving



	XL 10S	XL 25S
<b>Lumen</b>	1300lm	2800lm
<b>Power Consumption</b>	30W	65W
<b>Colour Temperature</b>	6500K (Daylight)	
<b>Life Span / IP Rating</b>	35,000 hours / IP54	
<b>Dimension (mm) HxWxD</b>	223 x 212 x 211	304 x 214 x 211

## XL 10S / XL 25S

### LED Sensor Floodlight

- Motion sensor controlled LED floodlight for various indoor and outdoor applications
- Can be programmed to operate during low light level
- Suitable for walkway, car porch, garden and low usage areas
- IP54 compliant - dust-proof, splash-proof and insect-proof
- 40% energy saving



	LE 27G60-5	LE 27G60-7
<b>Lumen</b>	240lm	400lm
<b>Power Consumption</b>	5W	7W
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)	
<b>Life Span</b>	35,000 hours	
<b>Dimension (mm) LxDia</b>	116 x 62	

## AZCEND Globe

### 5-Watt / 7-Watt LED Light Bulb

- Direct replacement for standard E27 base incandescent bulb
- Equivalent to 25W / 40W incandescent brightness
- Suitable for household, commercial and decorative lighting
- Die cast heat sink reduces operating temperature
- Frosted glass diffuser
- 80% energy saving



	LE27N40-6
<b>Lumen</b>	300~400lm
<b>Power Consumption / Beam Angle</b>	6W / 40°
<b>Colour Temperature</b>	3000K (Warm White), 4000K (Cool White), 6500K (Daylight)
<b>Life Span</b>	35,000 hours
<b>Dimension (mm) LxDia</b>	107 x 62

## AZCEND Spot

### 6-Watt LED Spotlight

- Direct replacement for standard E27 base incandescent bulb
- Equivalent to 40W incandescent brightness
- Suitable for household, accent and ambient lighting
- Die cast heat sink reduces operating temperature
- Focus lighting with 40° beam angle
- 80% energy saving



Note : All specifications subject to change without prior notice.